

Thermo 90S



Advantages

- Integrated Control Unit
- Fault Diagnosis Facility
- Compact Size
- Low Maintenance Costs
- “Intelligent” Temperature Regulation
- Leakproof Water Pump
- Unique “Ferro Tech” Burner

Technical Data

			Petrol Variant	Diesel Variant
Rated Voltage		v	12	12 or 24
Rated Heat Output	Full Heat Control Range	kW	7.6 2.0—7.6	9.1 1.8—7.6
Fuel Consumption	Full Heat Control Range	ltrs/hr	1.0 0.25—1.0	1.10 0.19—0.9
Flow of Circulation Pump	(against 0.3 bar)	ltrs/hr	700	
Heater Electrical Input	Start Up Full Heat Control Range	W	95 83 37-83	95 90 37-83
Dimensions of Heater	l x b x h	mm	355 x 133 x 232	
Weight of Heater with dosing pump		kg	4.8	

Typical Applications

- Truck
- Marine Installations
- Buses
- Agricultural Machinery
- Vans and Small Buses

Webasto Product UK Limited

Webasto House
White Rose Way
Doncaster Carr
South Yorkshire
United Kingdom
DN4 5JH

Phone : +44 (0) 1302 322232
Fax : +44 (0) 1302 322231
E-Mail: info@webastouk.com

Co Reg No : 2191825
VAT Reg No : 504 2738 67