

Thermo Top E



Advantages

- Warmth and comfort of a pre-heated interior
- Screen defrost and demist (safety)
- Pre-heated engine—no more cold starts
- Instant Engine Response
- Reduced Engine Wear
- Reduced Engine Emissions
- Integrated Diagnostic Capability
- Integrated Control Unit
- Ceramic Glowpin Technology
- Unique 'Ferrotech' Burner Cartridge
- Supplementary Heat Option
- Summer Cooling Device Available

Technical Data

Rated Voltage		v	12	
Rated Heat Output	Full Heat	kW	4.2	
	Reduced Heat		2.5	
Fuel Consumption	Full Heat	Ltrs/hr	Petrol	Diesel
	Reduced Heat		0.54	0.47
			0.33	0.29
Heater Power Consumption (without circulation pump)	Full Heat	W	26	
	Reduced Heat		22	
Circulation Pump Power Consumption		W	14	
Dimensions of Heater	l x b x h	mm	214 x 106 x 168	
Dimensions of Circulation Pump	l x b x h	mm	95 x 61 x 61	
Weight of Heater		kg	2.9	
Flow of Circulation Pump	Against 0.14 bar		500 ltrs/hr	
Fuel Type			Petrol or Diesel	

Typical Applications

- Passenger Car
- Vans & Small Buses
- Mobile Workshops
- Marine Installations
- Caravans/Mobile Homes
- Electric Vehicles

Webasto Product UK Limited

Webasto House
White Rose Way
Doncaster Carr
South Yorkshire
United Kingdom
DN4 5JH

Phone : +44 (0) 1302 322232
Fax : +44 (0) 1302 322231
E-Mail: info@webastouk.com

Co Reg No : 2191825
VAT Reg No : 504 2738 67